

QuickSeam™ Pipe Flashing

1. Description

The Firestone QuickSeam™ Pipe Flashing is specifically designed to be used for flashing of rigid round penetrations of 25 mm to 152 mm. It is a pre-fabricated pipe boot with a QuickSeam tape laminated to the bottom of the flange of the boot. Each QuickSeam Pipe Flashing will fit various penetrations and shall be cut at correct pipe diameter before installation.



2. Preparation

Penetration must be clean of prior flashing and foreign materials. The surface of the Firestone RubberCover™ EPDM membrane must be prepared with QuickPrime™ Plus. Use of other products is not allowed.

3. Application

Cut along the top edge of the ring on the QuickSeam Pipe Flashing corresponding to the size of the pipe. Refer to the Firestone guidelines for specific installation instructions.

4. Coverage

One piece per penetration.

5. Characteristics

Technical	Molded Pipe Flashing	QuickSeam Tape
• Base	Molded EPDM	Rubber polymers
• Color	Black	Black
• Solvents	None	None
• Solids	100%	100%
• State	Cured	Cured
• Thickness	1.4 mm - 1.9 mm	0.7 mm
• Flange diameter	330 mm	
• Penetration outside diameter	25 mm – 152 mm	

6. Packaging/ Storage/ Shelf Life

Packaging	10 pieces per carton. Stainless steel - worm gear type clamps are included
Part number	W563581063

Storage: Store in original unopened containers at temperatures between 15°C and 25°C, in a well-ventilated place. Keep the material dry and out of direct sunlight until ready for application.

Shelf Life: 24 months can be expected if stored in above-mentioned conditions. Verify production date on each carton packaging. Shelf life will be reduced if exposed to higher temperatures. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories.

7. Precautions

Refer to Safety Data Sheet.

This document replaces any other document published previous. This sheet is meant to highlight Firestone product information based on latest knowledge and experience and is subject to change without notice (check the Firestone website for latest document version). Above mentioned values are based on tested samples and may vary within applicable tolerances. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. No Firestone representative is authorized to vary this disclaimer.