

Cleaner C-20



1. Description

The Firestone Cleaner C-20 is an alcohol-based degreaser with extremely fast evaporation properties, designed for efficiently removing all types of Firestone adhesives, sealants and other types of contamination from EPDM membranes, metal and many other solvent-resistant surfaces.

2. Preparation

Surfaces to be cleaned must be free of heavy dirt. Heavy dirt can be removed with soapy water before the Cleaner C-20 is used.

3. Application

Thoroughly spray the area to be treated, allow the contamination to dissolve and clean the area with a clean cotton rag. For stubborn contamination, apply the Cleaner C-20 and scrub the area with a Firestone QuickScrubber™. Afterwards, remove the dirt and excess cleaner with a clean cotton rag.

4. Coverage

Not applicable.

5. Characteristics

Technical	
• Base	Alcohol
• Color	Transparent
• Solvents	Naphtha, 2-Propanol
• Solids (%)	0%
• Specific gravity (g/cm ³)	0.7 ± 0.02
• Flash point	-26°C

6. Packaging / Storage / Shelf life/ Disposal

Packaging	500 ml spray cans, 12 cans/carton
Part Number	W563581086C

Storage: Store cans protected from the weather at moderate temperatures (15°-25°C) in a dry, well-ventilated area. Keep away from heat, sparks and open flame. Protect the cans from heat and direct sunlight until ready for application and do not expose to temperatures exceeding 50°C.

Shelf life: 12 months can be expected if stored under the above-mentioned conditions. Shelf life information is only a recommendation. The true expiration date highly depends on the history of storage and handling of the product. Quality and useability should thus always be verified.

Disposal: Spray cans must be collected by a specialized company for disposal.

7. Precautions

Refer to Safety Data Sheet. Extremely flammable. Keep away from possible ignition sources during storage and use. Do not smoke when using. Do not spray onto a naked flame or any incandescent material. Do not pierce or burn the cans, even after use. Do not smoke near or when using the product. Protect against electrostatic charges. Use only in well ventilated areas. Avoid prolonged inhalation, contact with skin and eyes. For professional use only. Keep out of reach of children.

This document replaces any other document published previous. This sheet is meant to highlight Firestone product information based on latest knowledge and experience and is subject to change without notice (check the Firestone website for latest document version). Above mentioned values are based on tested samples and may vary within applicable tolerances. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. No Firestone representative is authorized to vary this disclaimer.