



QuickSeam™ Conduit Flashing

1. Description

The Firestone QuickSeam™ Conduit Flashing is specifically designed to be used for flashing rigid round penetrations and conduits from 13 mm to 64 mm. It is a pre-fabricated pipe boot with a QuickSeam tape laminated to the bottom of the flange of the boot. Each Conduit Flashing will fit various penetrations and shall be cut at the correct pipe diameter before installation.



2. Preparation

The penetration must be clean of prior flashing and foreign materials. The surface of the RubberGard™ EPDM membrane must be prepared with QuickPrime™ Plus. Use of other products is not allowed.

3. Application

Cut along the top edge of the ring on the QuickSeam Conduit Flashing corresponding to the size of the pipe. Refer to the Firestone guidelines for specific installation instructions.

4. Coverage

One piece per penetration.

5. Characteristics

| Technical | Molded Pipe Flashing | QuickSeam Tape |
|--------------------------------|----------------------|-----------------|
| • Base | Molded EPDM | Rubber polymers |
| • Color | Black | Black |
| • Solvents | None | None |
| • Solids | 100% | 100% |
| • State | Cured | Cured |
| • Thickness | 1.4 mm - 1.9 mm | 0.7 mm |
| • Flange diameter | 229 mm | |
| • Penetration outside diameter | 13 mm - 64 mm | |

6. Packaging / Storage / Shelf Life

| | |
|-------------|--|
| Packaging | 10 pieces per carton. Stainless steel - worm gear type clamps are included |
| Part number | W563581070 |

Storage: Store in original unopened containers at temperatures between 15°C and 25°C, in a well-ventilated place. Keep the material dry and out of direct sunlight until ready for application.

Shelf Life: 24 months can be expected if stored in above-mentioned conditions. Verify production date on each carton packaging. Shelf life will be reduced if exposed to higher temperatures. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories.

7. Precautions

Refer to Safety Data Sheet.

This document replaces any other document published previous. This sheet is meant to highlight Firestone product information based on latest knowledge and experience and is subject to change without notice (check the Firestone website for latest document version). Above mentioned values are based on tested samples and may vary within applicable tolerances. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. No Firestone representative is authorized to vary this disclaimer.