



## Splice Wash (SW-100)

### 1. Description

The Firestone Splice Wash SW-100 is designed to clean and prepare contaminated RubberGard™ EPDM membranes in areas to receive adhesives where required by Firestone specifications and details. Do not use it as a pre-wash for any QuickSeam™ Tape product; QuickPrime™ Plus must be used for QuickSeam™ Tape Products.



### 2. Preparation

Surfaces to be cleaned must be free of heavy dirt. Heavy dirt can be removed with soapy water before the Splice Wash is used.

### 3. Application

Apply Splice Wash to the splicing area using clean cotton rags in a scrubbing motion until the splicing surface is dull black in color. Take extra care at factory seams and allow the washed surfaces to dry. The membrane is clean when it is uniformly dark gray in color without streaks.

### 4. Coverage

Coverage rate is approximately 20 m<sup>2</sup> per gallon (1 side).

### 5. Characteristics

Physical	
• Flammable liquid	
• Thin, clear color liquid, hydrocarbon odor	
Technical	
• Base	Solvent Naphtha (Petroleum)
• Color	Clear
• Solvents	Aliphatic hydrocarbon mixture
• Solids	0 %
• Viscosity	Very thin, free flowing
• Density (g/cm <sup>3</sup> )	0.76
• Flash point	10°C

### 6. Packaging / Storage / Shelf Life

Packaging	4 x 3.78 L (1 gallon) cans/carton and 18.9 L (5 gallon) pail
Part number	W563587066E (4 x 3.78 L) W563587066 (18.9 L)

**Storage:** Dry and clean. Store in original unopened containers, in a cool, well-ventilated place (between 15°C to 25°C), away from any heat and ignition sources, until ready for use. Protect the cans from heat and direct sunlight.

**Shelf Life:** 24 months, when stored in the above-mentioned conditions. Verify the production date on each pail. Shelf life will be reduced if exposed to higher temperatures.



## 7. Precautions

- For professional use only.
- To prevent entry into waterways, sewers, basements, or confined areas, cover or stay away from all drains and roof openings. Make sure that no solvents can enter the building via ventilation openings (air intake or windows).
- Flammable. Use only in well-ventilated areas. Keep the container tightly closed and away from fire, sparks, and heated surfaces.
- Avoid prolonged inhalation and skin/eye contact. In case of contact, immediately flush skin/eyes with running water for at least 20 minutes. Wash skin with soap and water.
- Thinning is not allowed.
- Refer to Safety Data Sheets for additional info.

*This document replaces any other document published previously. This sheet is meant to highlight Firestone product information based on latest knowledge and experience and is subject to change without notice (check the Firestone website for latest document version). Above mentioned values are based on tested samples and may vary within applicable tolerances. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. No Firestone representative is authorized to vary this disclaimer.*