

Metal Batten Strip

1. Description

Firestone Metal Batten Strips are designed for the mechanical attachment of the RubberGard™ EPDM roofing membrane and flashing details as per Firestone specifications and details.



2. Preparation

All cut edges of metal batten strips must be rounded and filed to remove burrs and sharp edges. Remove any shavings from the roof.

3. Application

Layout the Metal Batten Strips as specified and attach them to the substrate using the appropriate Firestone fasteners. To avoid buckling of the strip it is recommended to start at one end of the batten strip and fasten towards the other end and to install all fasteners at proper depth. Set the fastener head flush with the strip. Do not overdrive or underdrive the fastener. Adjoining strips need to overlap and are to be fastened using one single fastener in the overlapping hole.

4. Coverage

In compliance with wind design requirements and as per Firestone Technical Guidelines.

5. Characteristics

Technical	
• Material	Galvalume® AZ55
• Length	Strip of 3.05 m
• Width	25.4 mm
• Thickness	1.1 mm/ 1.2 mm
• Holes	diam. 7.1 mm at 152 mm o.c.

6. Packaging / Storage / Shelf Life

Packaging	50 pieces (of 3.05 m)/cardboard tube (152.4 m)
Part number	W56RAC3053

Storage: Dry and clean in original unopened packaging protected from the weather.

Shelf Life: Unlimited, if stored in above-mentioned conditions.

This document replaces any other document published previous. This sheet is meant to highlight Firestone product information based on latest knowledge and experience and is subject to change without notice (check the Firestone website for latest document version). Above mentioned values are based on tested samples and may vary within applicable tolerances. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. No Firestone representative is authorized to vary this disclaimer.