



## Termination Bar

### 1. Description

The Firestone Termination Bar is an aluminium profile in C-shape that is designed for attachment and termination of the RubberGard™ EPDM membrane against upstands with a smooth and even finishing surface such as concrete, steel, etc.



### 2. Preparation

Substrate must be sound, smooth, dry and free from dust, dirt, oil and other contaminants prior to installation. Wall substrates above the Termination Bar must be waterproof. All cut edges must be rounded and filed to remove burrs and sharp edges. Remove any shavings from the roof.

### 3. Application

Apply a bead of Firestone Water Block Seal between the flashing membrane and the wall at 20 mm from the edge. Anchor the Termination Bar through the pre-punched holes with an acceptable fastener at a rate to maintain a good, tight compression of the Water Block Seal against the wall (maximum 200 mm). Install flat side towards flashing. Remove all excess of mastic that exceeds above the bar and apply Lap Sealant or another high grade sealant into the channel on top. Refer to the Firestone guidelines for specific installation instructions.

### 4. Coverage

In accordance with the length of the detail.

### 5. Characteristics

Technical	
• Material	Corrosion-resistant aluminum
• Length	3.05 m
• Width	27.4 mm
• Thickness	2.2 mm
• Holes	7.1 x 9.9 mm slotted holes at 100 mm o.c.

### 6. Packaging / Storage / Shelf Life

Packaging	50 pieces (of 3.05m)/cardboard tube (152.4 m)
Part number	W56RAC3061

**Storage:** Dry and clean in original unopened packaging protected from the weather.

**Shelf Life:** Unlimited, if stored in above-mentioned conditions.

This document replaces any other document published previous. This sheet is meant to highlight Firestone product information based on latest knowledge and experience and is subject to change without notice (check the Firestone website for latest document version). Above mentioned values are based on tested samples and may vary within applicable tolerances. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. No Firestone representative is authorized to vary this disclaimer.